

➤ *UPS Towable Passenger Stair*



Air-portable Passenger Stair (NSN-1730-99-912-2145)

Air-portable passenger stair for tactical and strategic passenger handling at both main and deployed operating bases. With a height range of 2.2m – 5.8m the UPS is suitable for all aircraft from MD80 up to B747 and A340.

- Robust and simple, offering low long term cost of ownership.
- Compact design with superb manoeuvrability ensuring ease of positioning at the aircraft threshold and within the aircraft for transportation.
- Efficient, stable, safe and effective.
- Ideal telescopic stair section promotes passenger confidence and security.
- Available with diesel or electric powered Pedestrian Drive System incorporating purpose designed hydrostatic drive system and finger tip control for a single operator.
- Heavy duty hydraulic stabilisers.
- Automatic mechanical stair locking pawls.
- Low voltage LED stair lighting.
- Spring loaded self aligning top platform nose section.
- Corrosion resistant materials.
- Shot blasted and finish painted to customers individual livery requirements with full wax treatment.
- Designed for air-transportation by C130, IL76 or other similar aircraft.
- Preparation for air-transport within 20 minutes.



Passenger Stairs

Belt Loaders
Cargo & Freight Vehicles
Toilet & Water Trucks
Aircraft Loaders
Fuel Tank Repair Trolleys
Heater Trolley
Air Conditioning Trolley
Maintenance Docks & Stagings
Special Projects

Remember, each piece of equipment is maintained via our through-life support and training services – wherever you are in the world, 365 days of the year.

T +44 (0)1656 743700
E office@amss.co
W www.amss.co

“ An essential piece of logistical support equipment offering rapid deployment capability ”

▶ UPS Towable Passenger Stair

Stair dimensions

- Nominal tread depth 276mm (11")
- Nominal tread width 1,000mm (39") (lower section)
- Nominal tread width 1,240mm (49") (upper section)
- Top Platform width 1,750mm (69")
- Intermediate landing 900mm (35") depth
- Constant riser 196mm (8")

Shipping dimensions

- Length 7,680mm (302")
- Width 2,260mm (89")
- Height 3,700mm (146")

Shipping weight

- Approx 3,600kg (7,920lb)

Height range

- Low Position 2,440mm (96")
- High Position 5,600mm (220")

Standard features

- Hydraulically powered stair elevation
- Diesel and electric powered pedestrian drive
- LED stair lighting
- Hydraulically powered stabilisers
- Stainless steel stair elevation running gear
- Air-portable in C130, IL76 and other similarly rated aircraft

